



Summary

Request a quote

Low Voltage	1
Wire Size/AWG	32 - 28
Jacket cable outside diameter [mm]	0.00 - 0.00 mm
Series	B - Indoor keyed

Technical details

Electrical Configuration

Contact Dia.	0.5
Low Voltage	1
Wire Size/AWG	32 - 28
Form & Material	
Shell style / Model id	FG - Male crimp contact, standard barrel
Shell style / Model id Housing material	FG - Male crimp contact, standard barrel Gold plated [ISO 27874] brass
	· · · · · · · · · · · · · · · · · · ·
Housing material	Gold plated [ISO 27874] brass

$\underline{https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/fgg-0b-554-zzc.html}$

Environment

Technical domain	Audio Video, Energy and Industrial, Medical, Semiconductor, Specialties and Other, Test and Measurement, Transportation, Aerospace and UAV	
Environmental protection	No IP rating	
Temp (min / max)	-55°C / +250°C	
Climatical Category	50/175/21	
Humidity (max)	<=95% [at 60 deg C /140 F]	
Shielding (min)	75 dB (10 MHz)	
Shielding (min)	40 dB (1 GHz)	
Shock Resistance	100 g [6 ms]	
Vibration	15 g [10 Hz - 2000 Hz]	
Cable fixation		
Cable termination protection	Standard back nut (no additional protection)	

Drawings



No keying

Dimensions

	Α	С
mm.	0.5	0.45
in.	0.02	0.02

Recommended By Lemo

Accessories

Tools		
Positionner	DCE.91.050.BVC	
Extraction tool	DCC.05.02B.LAG	
Crimp tool	DPC.91.701.V	

$\underline{https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/fgg-0b-554-zzc.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.